# **Product datasheet**

Specifications

#### Green Premium<sup>™</sup>



## Enclosure for modular device, Mureva Enclosure, 3x12 modules, earth terminal block

13985

#### Main

| Range                      | Mureva                       |
|----------------------------|------------------------------|
| Product Name               | Mureva Enclosure             |
| Product Or Component Type  | Weatherproof enclosure       |
| Enclosure Type             | Enclosure for modular device |
| Mounting Plate Description | Slotted                      |

## Complementary

| Complementary                      |  |
|------------------------------------|--|
| Enclosure Mounting                 | Surface  |
| 9 Mm Pitches                       | 24   |
| Number Of 18 Mm Modules Per<br>Row | 12   |
| Total Number Of 18 Mm Modules      | 36   |
| Number Of Horizontal Rows          | 3  |
| Electrical Insulation Class        | Double insulation<br>Class II  |
| Provided Equipment                 | 3 marking kit<br>3 wiring strap<br>1 terminal block 32 holes<br>1 terminal block support |
| Type Of Front Cover                | Transparent<br>Reversible  |
| Power Dissipation In W             | 46 W   |
| [In] Rated Current                 | 125 A  |
| Type Of Rail                       | DIN  |
| Number Of Pre-Cutouts Pg Iso       | 17   |
| Number Of Terminal Blocks          | 1 earth (screw connection) with 32 outgoers  |
| Distribution Block Outgoers        | 16 x 16 mm <sup>2</sup> + 16 x 10 mm <sup>2</sup>  |
| Locking Options Description        | Optional keylock   |
| Enclosure Material                 | Self-extinguishing polymer   |
| Width                              | 340 mm   |
| Height                             | 610 mm   |
| Depth                              | 160 mm   |
| Internal Depth                     | 88 mm  |
| Colour                             | Door: transparent green<br>Enclosure: light grey (RAL 7035)                              |

#### Environment

| Standards                                | IEC 61439-3<br>IEC 60695-2-1<br>EN 50262<br>IEC 60670   |  |
|--|---|--|
| Fire Resistance                          | 650 °C conforming to IEC 60695-2-1  |  |
| Ip Degree Of Protection                  | IP65 conforming to IEC 60529  |  |
| Ik Degree Of Protection                  | IK09 conforming to EN 50102   |  |
| Environmental Characteristics<br>(Uv)    | UV resistant: class 3 conforming to ISO 4582:2010<br>Ultraviolet degradation test conforming to ISO 4892-2:2013 |  |
| Overvoltage Category                     | II  |  |
| Ambient Air Temperature For<br>Operation | -2560 °C  |  |

## **Packing Units**

| Unit Type Of Package 1       | PCE        |
|------------------------------|------------|
| Number Of Units In Package 1 | 1          |
| Package 1 Height             | 16.800 cm  |
| Package 1 Width              | 35.500 cm  |
| Package 1 Length             | 62.000 cm  |
| Package 1 Weight             | 4.375 kg   |
| Unit Type Of Package 2       | P12        |
| Number Of Units In Package 2 | 22         |
| Package 2 Height             | 116.000 cm |
| Package 2 Width              | 80.000 cm  |
| Package 2 Length             | 120.000 cm |
| Package 2 Weight             | 108.250 kg |

## **Contractual warranty**

Warranty

18 months

### Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



Lower Impact Materials Transparency RoHS/REACh

#### **Resource performance**

Minimum Percentage Of Recycled 27 Plastic Content

#### Well-being performance

| Rohs Exemption Information | Yes |
|----------------------------|-----|
| Halogen Free Product       |     |

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Pro-active compliance (Product out of EU RoHS legal scope)  |
| China Rohs Regulation    | China RoHS declaration<br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | No need of specific recycling operations  |