## **Product datasheet**

Specifications





# Quantum RIO Drop E/IP 1CH - conformal coated

140CRA31200C

- (!) To be discontinued on: 31 Dec 2029
- (!) To be end-of-service on: 31 Dec 2037

## Main

Range Of Product	Modicon Quantum
Product Or Component Type	Ethernet RIO drop adaptor
Number Of Port	3
Integrated Connection Type	Ethernet IP/Modbus TCP for service port Ethernet IP/Modbus TCP for device network
Communication Port Protocol	Ethernet IP/Modbus TCP
Communication Service	Output modules are updated with the data received from remote I/O head adaptor The input data are collected and published to the remote I/O head adaptor

## Complementary

Тороlogy	Daisy chain loop
Local Signalling	1 LED (green/red) for module status (Mod Status) 1 LED (green/red) for network communication status (Net Status) 1 LED (green) for RUN 1 LED (red) for I/O
Product Compatibility	140CRP31200
Environmental Characteristic	Hazardous location class I division 2 conforming to EN/IEC 61131-1 Harsh environment
Width	167 mm
Height	50 mm
Net Weight	0.554 kg

## Environment

Product Certifications	UL 508 CE C-Tick
Standards	EN 55011 IEC 61000-4-16 CSA C22.2 No 142
Ip Degree Of Protection	IP20 conforming to EN 61131-2 IP20 conforming to IEC 60527
Overvoltage Category	Class I conforming to EN 61131-2
Ambient Air Temperature For Operation	060 °C conforming to IEC 60068-2-2 060 °C conforming to IEC 60068-2-2
Ambient Air Temperature For Storage	-4085 °C conforming to IEC 60068-2-2 -4085 °C conforming to IEC 60068-2-2

Vibration Resistance	3.5 mm constant amplitude (f= 0.58.4 Hz) conforming to EN 61131-2 1 gn constant acceleration (f= 8.4150 Hz) conforming to EN 61131-2
Operating Altitude	2000 m
Maximum Altitude Transport	3000 m
Relative Humidity	93 % conforming to IEC 60068

## **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	5.000 cm
Package 1 Width	16.500 cm
Package 1 Length	32.000 cm
Package 1 Weight	609.000 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	2
Package 2 Height	15.000 cm
Package 2 Width	30.000 cm
Package 2 Length	40.000 cm
Package 2 Weight	5.000 kg

## **Contractual warranty**

Warranty

18 months

## Sustainability Screen Premium

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

## Well-being performance

Reach Free Of Svhc

Mercury Free

Rohs Exemption Information Yes


### **Certifications & Standards**

Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins
Circularity Profile	End of Life Information

#### **Dimensions Drawings**

#### **Racks for Modules Mounting**

#### **Dimensions of Modules and Racks**



- (1) 2 slots
- (2) 3 slots
- (3) 4 slots
- (4) 6 slots
- (5) 10 slots
- (6) 16 slots