

Product datasheet

Specifications



Changeover relay RLI 10A 2P Uc 12VAC Ue 250VAC

15538

⚠ Discontinued on: 17 Nov 2014

⚠ End-of-service on: 2 Apr 2019

⚠ Discontinued

Main

Range Of Product	Multi9
Product Name	Multi9 RLI
Product Or Component Type	Relay
Device Short Name	RLI
Device Application	Changeover relay
Signal Contacts Composition	1 C/O + 1 NO
[Uc] Control Circuit Voltage	12 V AC 50/60 Hz

Complementary

[Ie] Rated Operational Current	10 A at 230 V AC (cos Phi = 1)
[Ui] Rated Insulation Voltage	250 V AC
Supply Holding Power	4 VA
Supply Inrush Power	4 VA
Mounting Mode	Fixed
Mounting Support	35 mm symmetrical DIN rail
9 Mm Pitches	2
Electrical Durability	AC-21: 100000 cycles
Connections - Terminals	Tunnel type terminals 0.5...6 mm²

Environment

Standards	IEC 255 NF C 45-250
-----------	------------------------

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	8.5 cm
Package 1 Width	1.8 cm
Package 1 Length	7.3 cm
Package 1 Weight	0.119 kg

Contractual warranty

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Warranty

18 months