

Product datasheet

Specifications



current transformer TI 250/5 A - for Linergy bar 800 to 1600 A

16477

⚠ Discontinued on: 1 Jan 2008

⚠ Discontinued

Main

| | |
|---------------------------|---|
| Range | PowerLogic |
| Product Name | CT |
| Product Or Component Type | Current transformer |
| Secondary Current | 5 A |
| Accuracy Class | Class 0.5 at 1 VA Class 1 at 4 VA Class 3 at 6 VA |
| [In] Rated Current | 250 A |

Complementary

| | |
|--------------------------------|--------------------------------|
| Current Transformer Type | Tropicalised for busbar |
| Current Transformer Ratio | 250/5 |
| Maximum Safety Factor | 5 |
| [Ue] Rated Operational Voltage | < 720 V AC 50/60 Hz |
| Mounting Mode | Insulated locking screw |
| Mounting Support | Busbar |
| Width | 32 mm inner: 90 mm outside: |
| Height | 65 mm inner: 90 mm outside: |
| Depth | 87 mm outside: |
| Net Weight | 0.6 kg |
| Opening Of Bars | 65 x 32 |
| Sealing | With |

Environment

| | |
|---------------------------------------|-------------------------|
| Standards | VDE 0414 IEC 60044-1 |
| Product Certifications | CE |
| Ip Degree Of Protection | IP20 |
| Relative Humidity | 95...100 % |
| Ambient Air Temperature For Operation | -25...60 °C |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|