

Product datasheet

Specifications



current transformer TI 800/5 A - for insulated flexible bar 65 x 32 mm

16482

⚠ Discontinued on: 17 Nov 2014

⚠ End-of-service on: 11 Oct 2023

⚠ Discontinued

Main

Range	PowerLogic
Product Name	CT
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 0.5 at 12 VA Class 1 at 15 VA Class 3 at 20 VA
[In] Rated Current	800 A

Complementary

Current Transformer Type	Tropicalised for busbar
Current Transformer Ratio	800/5
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
Mounting Mode	Insulated locking screw
Mounting Support	Busbar
Width	32 mm inner: 90 mm outside:
Height	65 mm inner: 90 mm outside:
Depth	87 mm outside:
Net Weight	0.6 kg
Opening Of Bars	65 x 32
Sealing	With

Environment

Standards	IEC 60044-1 VDE 0414
Product Certifications	CE
Ip Degree Of Protection	IP20
Relative Humidity	95...100 %
Ambient Air Temperature For Operation	-25...60 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Eu Rohs Directive	Compliant
	EU RoHS Declaration
<hr/>	
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information
<hr/>	