

# Product datasheet

Specifications



## current transformer TI 600/5 A - for canon Ø 23 mm - L 62 mm

16515

 **Discontinued on:** 1 Jan 2008

 **Discontinued**

### Main

Range	PowerLogic
Product Name	CT
Product Or Component Type	Current transformer
Secondary Current	5 A
Accuracy Class	Class 3 at 26 VA Class 0.5 at 14.5 VA Class 1 at 21.5 VA
[In] Rated Current	600 A

### Complementary

Current Transformer Type	Standard for busbar and cable
Current Transformer Ratio	600/5
Maximum Safety Factor	5
[Ue] Rated Operational Voltage	< 720 V AC 50/60 Hz
Mounting Mode	Insulated locking screw
Mounting Support	Mounting plate DIN rail Busbar
Width	56 mm outside:
Height	88.5 mm outside:
Depth	60 mm outside:
Diameter	22 mm
Net Weight	0.27 kg
Cable Outer Diameter	22 mm - cable 0...150 mm <sup>2</sup>
Opening Of Bars	30 x 10

### Environment

Standards	IEC 60044-1 VDE 0414
Product Certifications	CE
Ip Degree Of Protection	IP20
Relative Humidity	0...95 %
Ambient Air Temperature For Operation	-5...55 °C

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

# Contractual warranty

Warranty	18 months
----------	-----------