

Product datasheet

Specifications



Acti9, Remote indication auxiliary, Acti9 iACTs, 1 NO + 1 NC

A9C15914

Main

Range Of Product	ICT
Range	Acti9
Device Short Name	iACTs
Product Or Component Type	Remote indication auxiliary
Signal Contacts Composition	1 NO + 1 NC

Complementary

Signalling Circuit Voltage	24 V AC/DC: 10 mA 230 V AC: 50/60 Hz 5 A 230 V AC: 50/60 Hz 2 A 130 V DC: 1 A
[Uc] Control Circuit Voltage	24...240 V AC 50/60 Hz 24...130 V DC
Range Compatibility	Acti 9 Acti9 iCT
[Ui] Rated Insulation Voltage	440 V
[Uimp] Rated Impulse Withstand Voltage	4 kV
Mounting Mode	Fixed, on the right of CT
Mounting Support	35 mm symmetrical DIN rail
9 Mm Pitches	1
Height	81 mm
Width	9 mm
Depth	68 mm
Colour	White
Auxiliary Connection Terminal	Tunnel type terminals2 cable(s) flexible 2.5 mm² Tunnel type terminals2 cable(s) rigid 1.5 mm² Tunnel type terminals1 cable(s) rigid 1.5...2.5 mm² Tunnel type terminals1 cable(s) flexible 1.5...2.5 mm²
Wire Stripping Length	9 mm
Tightening Torque	0.8 N.m
Product Compatibility	ICT
Market Segment	Small commercial Residential
Compatibility Code	iACTs

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	EN 60947-5
Ip Degree Of Protection	IP20 IP20 conforming to IEC 60529
Tropicalisation	2
Relative Humidity	95 % at 55 °C
Ambient Air Temperature For Operation	-5...50 °C
Ambient Air Temperature For Storage	-40...70 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.2 cm
Package 1 Width	7.5 cm
Package 1 Length	8.5 cm
Package 1 Weight	43.0 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	10
Package 2 Height	8.1 cm
Package 2 Width	9.3 cm
Package 2 Length	22.8 cm
Package 2 Weight	490.0 g
Unit Type Of Package 3	S03
Number Of Units In Package 3	120
Package 3 Height	30.0 cm
Package 3 Width	30.0 cm
Package 3 Length	40.0 cm
Package 3 Weight	6.36 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

✓	Reach Free Of Svhc	
✓	Toxic Heavy Metal Free	
✓	Mercury Free	
✓	Rohs Exemption Information	Yes
✓	Halogen Free Product	
Reach Regulation	REACH Declaration	
Eu Rohs Directive	Compliant EU RoHS Declaration	
China Rohs Regulation	China RoHS declaration	
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	