


Product datasheet

Specifications

Acti9, comb busbar - 1L+N with Aux - 9 mm pitch - 56 modules - 63A



A9N21035

⚠ Discontinued on: 24 June 2013

⚠ To be end-of-service on: 15 Aug 2024

⚠ Discontinued

Main

Range	Acti9
Product Or Component Type	Comb busbar
Mounting Mode	Horizontal
Accessory / Separate Part Category	Connection accessory
Lines Description	1L + N
Length In 18 Mm Modules	56

Complementary

Number Of Ways	37 ways Aux + N + 1 L
Poles Configuration For 1 Way	1 x 1P + N
Connection Pitch	9 mm between phase and neutral
Connector Type	Tooth
Distance Between Way	27 mm
Marking	N L
Insulation	Insulated
Device Presentation	Cuttable
[Ie] Rated Operational Current	63 A at 40 °C
[Ue] Rated Operational Voltage	230 V AC Ph/N
[Ui] Rated Insulation Voltage	500 V AC conforming to IEC 61439-2
Mounting Location	Top on tunnel type terminals
9 Mm Pitches	112
Width	1000 mm
Colour	Light grey (RAL 7035)
Range Compatibility	Acti 9 Acti9 C40 Acti 9 Acti9 C40 Vig Acti 9 Acti9 DT40 Acti 9 Acti9 DT40 Vig Acti 9 Acti9 iDPN Acti 9 Acti9 iDPN Vig Acti 9 Acti9 ID C40 Acti 9 Acti9 IDc Acti 9 Acti9 ITG40 Multi9 Multi9 N40

Environment

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	IEC 60947-7-1 IEC 61439-2
Fire Resistance	960 °C (30 s) conforming to IEC 60695-2-1
Pollution Degree	3 conforming to IEC 60947-7-1
Ip Degree Of Protection	IP20 with end-pieces and tooth covers

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.000 cm
Package 1 Width	12.000 cm
Package 1 Length	101.000 cm
Package 1 Weight	595.000 g
Unit Type Of Package 2	BB1
Number Of Units In Package 2	5
Package 2 Height	6.000 cm
Package 2 Width	101.000 cm
Package 2 Length	12.000 cm
Package 2 Weight	2.978 kg
Unit Type Of Package 3	P12
Number Of Units In Package 3	80
Package 3 Height	75.000 cm
Package 3 Width	80.000 cm
Package 3 Length	120.000 cm
Package 3 Weight	59.648 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability

Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

 Reach Free Of Svhc	
 Toxic Heavy Metal Free	
 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Compliant EU RoHS Declaration
China Rohs Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins