Product datasheet

Specification





Easy56, Plug, 3 Pin, 15A, 250V

EY56P315

Main

Product Name	Easy56
Product Or Component Type	Plug
Device Short Name	EY56P315
Plug, Socket Category	Low voltage
Poles Description	1P + N + E
Pin Number	3 pins
Shape Of Pin	Flat
Outlet Standard Deviation	Australian/New Zealand

Complementary

Plug, Socket, Control Station Shape	Straight
[In] Rated Current	15 A
[Ue] Rated Operational Voltage	250 V
Network Type	AC
Network Frequency	50 Hz
Material	Polycarbonate: housing
Contacts Material	Pins: brass
Connections - Terminals	Screw terminals
Cable Cross Section	1.5 mm²
Cable Outer Diameter	7.410.6 mm
Wire Stripping Length	1234 mm
Cable Entry	Cable gland
Thread Type	M20
Net Weight	0.107 kg
Height	67 mm
Width	67 mm
Depth	112.5 mm
Colour	Plug: orange (RAL 2004) Body: clear

Environment

Standards AS/NZS 3112

Quality Labels	RCM
Ip Degree Of Protection	IP66 conforming to AS 60529
Ambient Air Temperature For Operation	-2575 °C
Ambient Air Temperature For Storage	-2575 °C

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	6.8 cm
Package 1 Width	8.1 cm
Package 1 Length	11.2 cm
Package 1 Weight	112 g



Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO2 products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance



Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information
Environmental Disclosure	Product Environmental Profile
Circularity Profile	No need of specific recycling operations