# **Product datasheet**

Specifications



## Easy56, Plug, 4 Pin, 10A, 500V

EY56P410

#### Main

Product Name	Easy56
Product Or Component Type	Plug
Device Short Name	EY56P410
Plug, Socket Category	Low voltage
Poles Description	3P + E
Pin Number	4 pins
Shape Of Pin	Tubular
Outlet Standard Deviation	Australian/New Zealand

#### Complementary

eempionientary	
Plug, Socket, Control Station Shape	Straight
[In] Rated Current	10 A
[Ue] Rated Operational Voltage	500 V
Network Type	AC
Network Frequency	50 Hz
Material	Polycarbonate: housing
Contacts Material	Pins: brass
Connections - Terminals	Screw terminals
Cable Cross Section	14 mm <sup>2</sup>
Cable Outer Diameter	716 mm
Wire Stripping Length	1035 mm
Cable Entry	Cable gland
Net Weight	0.298 kg
Height	78 mm
Width	78 mm
Depth	152 mm
Colour	Plug: orange (RAL 2004) Body: clear

#### Environment

Standards	AS/NZS 3123
Ip Degree Of Protection	IP66 conforming to AS 60529

Ambient Air Temperature For Operation	-2575 °C
Ambient Air Temperature For Storage	-2575 °C

### **Packing Units**

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	17.0 cm
Package 1 Width	8.0 cm
Package 1 Length	9.5 cm
Package 1 Weight	313.0 g

#### **Sustainability**

**Green Premium<sup>TM</sup> label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >

#### Well-being performance

Rohs Exemption Information	Yes
Reach Regulation	REACh Declaration
Eu Rohs Directive	Compliant with Exemptions
China Rohs Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information