

Product datasheet

Specifications



CANopen slave unit, Harmony GTU, for Universal panel

HMIZGCAN

⚠ Discontinued on: 21 Dec 2020

⚠ End-of-service on: 25 Jan 2021

⚠ Discontinued

Main

Range Of Product	Harmony GTU
Product Or Component Type	CANopen slave unit

Complementary

Accessory / Separate Part Destination	Universal panel
Power Consumption In W	0.7 W
Input Voltage	3.3 V DC
Range Compatibility	Harmony GTU
Width	60 mm
Height	87 mm
Depth	41 mm
Net Weight	0.1 kg

Environment

Ambient Air Temperature For Operation	0...60 °C
Ambient Air Temperature For Storage	-20...60 °C
Relative Humidity	10...90 %
Ip Degree Of Protection	IP2
Vibration Resistance	3.5 mm constant amplitude (f= 5...9 Hz) conforming to EN/IEC 61131-2 9.8 m/s² (f= 9...150 Hz) conforming to EN/IEC 61131-2
Shock Resistance	147 m/s²
Product Certifications	IEC-Ex KC CE EAC RCM ATEX zone 2/22 UKCA UKEX

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Sustainability



Green Premium™ label is Schneider Electric’s commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product’s sustainability >](#)

Well-being performance

 Mercury Free	
 Rohs Exemption Information	Yes
Reach Regulation	REACH Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins