# **Product datasheet**

Specification





Circuit breaker, ComPact NSX400R, 200kA/415VAC, MicroLogic 5.3E trip unit 400A, 4 poles 4d

LV433607

(!) Discontinued on: 10 Nov 2022

! End-of-service on: 30 June 2023

#### ! Discontinued

#### Main

| Range   | ComPact  |
|---|--|
| Product Name  | ComPact NSX  |
| Range Of Product  | ComPact NSX400630  |
| Device Short Name                                       | NSX400R  |
| Product Or Component Type                               | Circuit breaker  |
| Device Application                                      | Distribution   |
| Number Of Poles   | 4P   |
| Protected Poles Description                             | 4t<br>3t + OSN<br>3t + N/2<br>3t   |
| Neutral Position  | Left   |
| [In] Rated Current                                      | 400 A at 40 °C   |
| [Ue] Rated Operational Voltage                          | 690 V AC 50/60 Hz  |
| Network Type  | AC   |
| Network Frequency                                       | 50/60 Hz   |
| Suitability For Isolation                               | Yes conforming to EN/IEC 60947-2   |
| Utilisation Category                                    | Category A   |
| [Icu] Rated Ultimate Short-Circuit<br>Breaking Capacity | 200 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 200 kA Icu at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 200 kA Icu at 440 V AC 50/60 Hz conforming to IEC 60947-2 80 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 45 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level                                       | R 200 kA 415 V AC  |
| Trip Unit Name  | MicroLogic 5.3 E   |
| Trip Unit Technology                                    | Electronic   |
| Trip Unit Protection Functions                          | LSI  |
| Control Type  | Toggle   |
| Circuit Breaker Mounting Mode                           | Fixed  |

### Complementary

| [Ui] Rated Insulation Voltage                                | 800 V AC 50/60 Hz  |
|--|--|
| [Uimp] Rated Impulse Withstand Voltage                       | 8 kV   |
| [Ics] Rated Service Short-Circuit<br>Breaking Capacity       | 200 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 200 kA at 380/415 V AC 50/60 Hz conforming to IEC 60947-2 200 kA at 440 V AC 50/60 Hz conforming to IEC 60947-2 80 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 65 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 45 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2 |
| Mechanical Durability  | 15000 cycles   |
| Electrical Durability  | 3000 cycles at 690 V In<br>6000 cycles at 690 V In/2<br>6000 cycles at 440 V In<br>12000 cycles at 440 V In/2  |
| Mounting Support   | Backplate  |
| Upside Connection  | Front  |
| Downside Connection  | Front  |
| Connection Pitch   | 45 mm  |
| Protection Type  | L : for overload protection (long time) S : for short time short-circuit protection I : for instantaneous short-circuit protection   |
| Trip Unit Rating   | 400 A at 40 °C   |
| Long-Time Pick-Up Adjustment<br>Type Ir (Thermal Protection) | Adjustable 9 settings  |
| [Ir] Long-Time Protection Pick-Up Adjustment Range           | 160400 A   |
| Long-Time Protection Delay<br>Adjustment Type Tr             | Adjustable   |
| [Tr] Long-Time Protection Delay<br>Adjustment Range          | 15400 s at 1.5 x lr<br>0.3511 s at 7.2 x lr<br>0.516 s at 6 x lr   |
| Thermal Memory   | 20 minutes before and after tripping   |
| Short-Time Protection Pick-Up<br>Adjustment Type Isd         | Adjustable 9 settings  |
| [Isd] Short-Time Protection Pick-<br>Up Adjustment Range     | 1.510 x lr   |
| Short-Time Protection Delay<br>Adjustment Type Tsd           | Adjustable 5 settings  |
| [Tsd] Short-Time Protection Delay Adjustment Range           | 00.4 s   |
| Instantaneous Protection Pick-Up<br>Adjustment Type Ii       | Adjustable   |
| [li] Instantaneous Protection Pick-<br>Up Adjustment Range   | 1.512 x ln   |
| Earth-Leakage Protection                                     | Without  |
| Neutral Protection Settings                                  | 0.5 x lr (3t + N/2)<br>1 x lr (4t)<br>1.6 x lr (3t + OSN)<br>No protection (3t)  |
| Zone Selective Interlocking Zsi                              | With   |
| Number Of Slots For Electrical<br>Auxiliaries                | 6 slot(s)  |
| Local Signalling   | Flashing LED (green) for ready to operate<br>LED 105 % Ir (red) for overload<br>LED 90 % Ir (orange) for overload  |
| Display Type   | LCD display  |
| Type Of Measurement  | Energy meter   |

| Communication Of Data | Time-stamped histories and event tables Instantaneous and demand values Power quality Energy metering Maximeters/minimeters Demand current and power Maintenance indicators Protection and alarm settings |
|-----------------------|---|
| Width (W)             | 185 mm  |
| Height (H)            | 255 mm  |
| Depth (D)             | 110 mm  |
| Net Weight            | 7.9 kg  |

### **Environment**

| Standards                             | EN/IEC 60947   |
|---------------------------------------|--|
| Product Certifications                | CCC<br>EAC<br>Marine                                   |
| Overvoltage Category                  | Class II   |
| Electrical Shock Protection Class     | Class II   |
| Pollution Degree                      | 3 conforming to IEC 60664-1                            |
| Ip Degree Of Protection               | IP40 conforming to IEC 60529                           |
| Ik Degree Of Protection               | IK07 conforming to IEC 62262                           |
| Ambient Air Temperature For Operation | -2570 °C   |
| Ambient Air Temperature For Storage   | -4085 °C   |
| Relative Humidity                     | 095 %  |
| Operating Altitude                    | 02000 m without derating<br>2000 m5000 m with derating |

## **Packing Units**

| Unit Type Of Package 1       | PCE      |
|------------------------------|----------|
| Number Of Units In Package 1 | 1        |
| Package 1 Height             | 15.2 cm  |
| Package 1 Width              | 20.3 cm  |
| Package 1 Length             | 29.2 cm  |
| Package 1 Weight             | 7.585 kg |

## **Contractual warranty**

Warranty 18 months

## Sustainability Green Premium

**Green Premium**<sup>TM</sup> **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO<sub>2</sub> products.

**Guide to assessing product sustainability** is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

### Well-being performance



Mercury Free



Rohs Exemption Information

Yes

#### **Certifications & Standards**

| Reach Regulation         | REACh Declaration   |
|--------------------------|---|
| Eu Rohs Directive        | Compliant with Exemptions   |
| China Rohs Regulation    | China RoHS declaration  Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure | Product Environmental Profile   |
| Circularity Profile      | End of Life Information   |