Product datasheet

Specifications





Circuit breaker, ComPact NSX400HB2, 100kA/690VAC, MicroLogic 6.3E-M trip unit 320A, 3 poles 3d

LV433650

() Discontinued on: 13 Nov 2022

(!) End-of-service on: 30 June 2023

Main

Range	ComPact	
Product Name	ComPact NSX	
Range Of Product	ComPact NSX400630	
Device Short Name	NSX400HB2	
Product Or Component Type	Circuit breaker	
Device Application	Motor	
Number Of Poles	3P	
Protected Poles Description	3t	
[In] Rated Current	320 A at 65 °C	
[Ue] Rated Operational Voltage	690 V AC 50/60 Hz	
Network Type	AC	
Network Frequency	50/60 Hz	
Suitability For Isolation	Yes conforming to EN/IEC 60947-2	
Utilisation Category	Category A	
[Icu] Rated Ultimate Short-Circuit Breaking Capacity	100 kA Icu at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA Icu at 660/690 V AC 50/60 Hz conforming to IEC 60947-2	
Performance Level	HB2 100 kA 690 V AC	
Trip Unit Name	MicroLogic 6.3 E-M	
Trip Unit Technology	Electronic	
Trip Unit Protection Functions	LSIG	
Control Type	Toggle	
Circuit Breaker Mounting Mode	Fixed	

Complementary

[Ui] Rated Insulation Voltage	800 V AC 50/60 Hz
[Uimp] Rated Impulse Withstand Voltage	8 kV
[Ics] Rated Service Short-Circuit Breaking Capacity	100 kA at 500 V AC 50/60 Hz conforming to IEC 60947-2 100 kA at 525 V AC 50/60 Hz conforming to IEC 60947-2 100 kA at 660/690 V AC 50/60 Hz conforming to IEC 60947-2

Mechanical Durability	15000 cycles	
Electrical Durability	3000 cycles at 690 V In	
	6000 cycles at 690 V In/2	
	6000 cycles at 440 V In 12000 cycles at 440 V In/2	
Manualian Ormanant	·	
Mounting Support	Backplate	
Upside Connection	Front	
Downside Connection	Front	
Connection Pitch	45 mm	
Protection Type	L : for overload protection (long time)	
	S : for short time short-circuit protection	
	I : for instantaneous short-circuit protection G : for ground fault protection	
Trin Unit Dating		
Trip Unit Rating	320 A at 65 °C	
Motor Tripping Class	30 20	
	5	
	10	
Complementary Motor Protection	Protracted starting time Underload	
	Phase unbalance	
	Stalled rotor	
Long-Time Pick-Up Adjustment Type Ir (Thermal Protection)	Adjustable 9 settings	
[Ir] Long-Time Protection Pick-Up Adjustment Range	160320 A	
Long-Time Protection Delay Adjustment Type Tr	Adjustable	
[Tr] Long-Time Protection Delay Adjustment Range	10 s at 7.2 x lr for trip class 10	
A guotinent hange	120 s at 1.5 x Ir for trip class 5 20 s at 7.2 x Ir for trip class 20	
	240 s at 1.5 x lr for trip class 10	
	26 s at 6 x Ir for trip class 20	
	480 s at 1.5 x lr for trip class 20	
	5 s at 7.2 x Ir for trip class 5 13.5 s at 6 x Ir for trip class 10	
	6.5 s at 6 x Ir for trip class 5	
	30 s at 7.2 x lr for trip class 30	
	38 s at 6 x Ir for trip class 30 720 s at 1.5 x Ir for trip class 30	
Thormal Momony	·	
Thermal Memory	20 minutes before and after tripping	
Short-Time Protection Pick-Up Adjustment Type Isd	Adjustable 9 settings	
[Isd] Short-Time Protection Pick- Up Adjustment Range	513 x lr	
Short-Time Protection Delay Adjustment Type Tsd	Fixed	
Instantaneous Protection Pick-Up Adjustment Type Ii	Fixed	
[li] Instantaneous Protection Pick- Up Adjustment Range	4800 A	
Ground-Fault Protection Pick-Up Adjustment Type Ig	Adjustable 9 settings	
[Ig] Ground-Fault Protection Pick- Up Adjustment Range	0.61 x ln for ln = 25 A	
	0.31 x ln for ln = 50 A 0.21 x ln for ln > 50 A	
	Ig enable on/off	
Ground-Fault Protection Time Delay Adjustment Type Tg	Adjustable	
[Tg] Ground-Fault Protection Time Delay Adjustment Range	00.4 s	
Earth-Leakage Protection	Without	
Zone Selective Interlocking Zsi	With	

Number Of Slots For Electrical Auxiliaries	6 slot(s)	
Local Signalling	Flashing LED (green) for ready to operate LED 95 % Ith (red) for temperature over set point	
Display Type	LCD display	
Type Of Measurement	Energy meter	
Communication Of Data	Demand current and power Maintenance indicators Thermal image function Power quality Maximeters/minimeters Energy metering Protection and alarm settings Time-stamped histories and event tables Phase sequence Instantaneous and demand values	
Width (W)	140 mm	
Height (H)	255 mm	
Depth (D)	110 mm	
Net Weight	6.05 kg	

Environment

Standards	EN/IEC 60947	
Product Certifications	Marine CCC EAC	
Overvoltage Category	Class II	
Electrical Shock Protection Class	Class II	
Pollution Degree	3 conforming to IEC 60664-1	
Ip Degree Of Protection	IP40 conforming to IEC 60529	
Ik Degree Of Protection	IK07 conforming to IEC 62262	
Ambient Air Temperature For Operation	-2570 °C	
Ambient Air Temperature For Storage	-4085 °C	
Relative Humidity	095 %	
Operating Altitude	02000 m without derating 2000 m5000 m with derating	

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	15.2 cm
Package 1 Width	15.2 cm
Package 1 Length	29.2 cm
Package 1 Weight	5.82 kg

Contractual warranty

Warranty

18 months

Sustainability Screen

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance

Mercury Free

Rohs Exemption Information

Certifications & Standards

Eu Rohs Directive	Compliant
	EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
	Product out of China RoHS scope. Substance declaration for your information
Weee	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins