Product datasheet

Specification





Circuit breaker, ComPact NSX100F AC/DC, 18kA/240VAC, TMD trip unit 50A, 1 pole 1d

LV438567

- ! Discontinued on: 31 Dec 2023
- ! End-of-service on: 21 Sept 2023

① Discontinued

Main

| Range | ComPact |
|--|--|
| Product Name | ComPact NSX |
| Range Of Product | ComPact NSX100250 ComPact NSX100250 DC |
| Device Short Name | NSX100F |
| Product Or Component Type | Circuit breaker |
| Device Application | Distribution |
| Number Of Poles | 1P |
| Protected Poles Description | 1t |
| [In] Rated Current | 50 A at 40 °C |
| [Ue] Rated Operational Voltage | 250 V DC 277 V AC 50/60 Hz |
| Network Type | DC AC |
| Network Frequency | 50/60 Hz |
| Suitability For Isolation | Yes conforming to EN/IEC 60947-2 |
| Utilisation Category | Category A |
| [Icu] Rated Ultimate Short-Circuit Breaking Capacity | 36 kA Icu at 250 V DC 1P conforming to IEC 60947-2 36 kA Icu at 125 V DC 1P conforming to IEC 60947-2 18 kA Icu at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 |
| Performance Level | F 18 kA 240 V AC |
| Trip Unit Name | TM-D |
| Trip Unit Technology | Thermal-magnetic |
| Control Type | Toggle |
| Circuit Breaker Mounting Mode | Fixed |

Complementary

| - | | |
|--|--|--|
| [Ui] Rated Insulation Voltage | 750 V AC 50/60 Hz conforming to IEC 60947-2 | |
| [Uimp] Rated Impulse Withstand Voltage | 8 kV conforming to IEC 60947-2 | |
| [lcs] Rated Service Short-Circuit Breaking Capacity | 36 kA at 250 V DC conforming to IEC 60947-2 36 kA at 125 V DC conforming to IEC 60947-2 18 kA at 220/240 V AC 50/60 Hz conforming to IEC 60947-2 | |
| Mechanical Durability | 20000 cycles | |

28 Apr 2024 Life Is On Schneider

| Electrical Durability | 10000 cycles at 277 V In 20000 cycles at 277 V In/2 |
|--|---|
| Mounting Support | Backplate |
| Upside Connection | Front |
| Downside Connection | Front |
| Connection Pitch | 35 mm |
| Protection Type | for overload protection (thermal) for short-circuit protection (magnetic) |
| Trip Unit Rating | 50 A at 40 °C |
| Long-Time Pick-Up Adjustment Type Ir (Thermal Protection) | Fixed |
| [Ir] Long-Time Protection Pick-Up Adjustment Range | 1 ln |
| [Im] Magnetic Protection Pick-Up Range | 500 A |
| Earth-Leakage Protection | Without |
| Width (W) | 35 mm |
| Height (H) | 161 mm |
| Depth (D) | 86 mm |

Environment

| Standards | EN/IEC 60947 |
|---------------------------------------|--|
| Product Certifications | CCC EAC Marine |
| Overvoltage Category | Class II |
| Electrical Shock Protection Class | Class II |
| Pollution Degree | 3 conforming to IEC 60664-1 |
| Ip Degree Of Protection | IP40 conforming to IEC 60529 |
| Ik Degree Of Protection | IK07 conforming to IEC 62262 |
| Ambient Air Temperature For Operation | -2570 °C |
| Ambient Air Temperature For Storage | -5085 °C |
| Relative Humidity | 095 % |
| Operating Altitude | 02000 m without derating 2000 m5000 m with derating |

Packing Units

| Unit Type Of Package 1 | PCE |
|------------------------------|---------|
| Number Of Units In Package 1 | 1 |
| Package 1 Height | 4.0 cm |
| Package 1 Width | 13.0 cm |
| Package 1 Length | 17.5 cm |
| Package 1 Weight | 733.0 g |
| Unit Type Of Package 2 | S03 |
| Number Of Units In Package 2 | 12 |
| Package 2 Height | 30.0 cm |

| Package 2 Width | 30.0 cm | |
|------------------|----------|--|
| Package 2 Length | 40.0 cm | |
| Package 2 Weight | 9.283 ka | |

Contractual warranty

Warranty 18 months



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >



RoHS/REACh

Well-being performance



Mercury Free



Rohs Exemption Information

Yes

Certifications & Standards

| Eu Rohs Directive | Compliant |
|-----------------------|---|
| | EU RoHS Declaration |
| China Rohs Regulation | China RoHS declaration Product out of China RoHS scope. Substance declaration for your information |