Specifications





Harmony Timer Relays, Modular timing relay, 8A, 1CO, 1s..100h, off delay, 24V DC 24...240V AC DC

RE17RCMU

Main

Range Of Product	Harmony Timer Relays
Product Or Component Type	Single function relay
Discrete Output Type	Relay
Width	17.5 mm
Device Short Name	RE17R
Time Delay Type	Off-delay
Time Delay Range	660 s 110 h 110 min 660 min 0.11 s 110 s 10100 h
Nominal Output Current	8 A

Complementary

Contacts Type And Composition	1 C/O
Contacts Material	Cadmium free
Height	90 mm
Depth	72 mm
Control Type	Selector switch front panel
[Us] Rated Supply Voltage	24240 V AC 50/60 Hz 24 V DC
Voltage Range	0.851.1 Us
Supply Frequency	5060 Hz +/- 5 %
Release Of Input Voltage	10 V
Connections - Terminals	Screw terminals, 1 x 0.51 x 3.3 mm ² (AWG 20AWG 12) solid without cable end Screw terminals, 2 x 0.52 x 2.5 mm ² (AWG 20AWG 14) solid without cable end Screw terminals, 1 x 0.21 x 2.5 mm ² (AWG 24AWG 14) flexible with cable end Screw terminals, 2 x 0.22 x 1.5 mm ² (AWG 24AWG 16) flexible with cable end
Tightening Torque	0.61 N.m conforming to IEC 60947-1
Housing Material	Self-extinguishing
Repeat Accuracy	+/- 0.5 % conforming to IEC 61812-1
Temperature Drift	+/- 0.05 %/°C
Voltage Drift	+/- 0.2 %/V
Setting Accuracy Of Time Delay	+/- 10 % of full scale at 25 °C conforming to IEC 61812-1

Control Signal Pulse Width	100 ms with load in parallel typical 30 ms typical	
Insulation Resistance	100 MOhm at 500 V DC conforming to IEC 60664-1	
Reset Time	120 ms on de-energisation typical	
On-Load Factor	100 %	
Power Consumption In Va	032 VA at 240 V AC	
Maximum Power Consumption In W	0.6 W at 24 V DC	
Minimum Switching Current	10 mA at 5 V DC	
Maximum Switching Current	8 A AC/DC	
Maximum Switching Voltage	250 V AC	
Breaking Capacity	2000 VA	
Operating Frequency	10 Hz	
Electrical Durability	100000 cycles (8 A at 250 V AC maximum) for resistive load	
Mechanical Durability	1000000 cycles	
Dielectric Strength	2.5 kV 1 mA/1 minute 50 Hz conforming to IEC 61812-1	
[Uimp] Rated Impulse Withstand Voltage	5 kV during 1.2/50 μs	
Power On Delay	100 ms	
Marking	CE	
Creepage Distance	4 kV/3 conforming to IEC 60664-1	
Safety Reliability Data	B10d = 270000 MTTFd = 296.8 years	
Mounting Position	Any position in relation to normal vertical mounting plane	
Mounting Support	35 mm DIN rail conforming to IEC 60715	
Local Signalling	LED indicator for on steady: relay energised, no timing in progress LED indicator for flashing: timing in progress 80 % ON and 20 % OFF LED indicator for pulsing: relay de-energised, no timing in progress (except function Di-D, Li-L) 5 % ON and 95 % OFF	
Net Weight	0.07 kg	
Number Of Functions	1	
Time Delay Type	C	
Functionality	Off-delay timing	
Compatibility Code	RE17	

Environment

Immunity To Microbreaks	20 ms
Standards	IEC 61000-6-4
	IEC 61000-6-2
	IEC 61000-6-3
	2004/108/EC
	2006/95/EC
	IEC 61812-1
	IEC 61000-6-1
Product Certifications	cULus
	GL
	CSA
Ambient Air Temperature For Storage	-3060 °C
Ambient Air Temperature For Operation	-2060 °C

Ip Degree Of Protection	IP20 (terminal block) conforming to IEC 60529
	IP40 (housing) conforming to IEC 60529
	IP50 (front panel) conforming to IEC 60529
Vibration Resistance	20 m/s ² (f= 10150 Hz) conforming to IEC 60068-2-6
Shock Resistance	15 gn for 11 ms conforming to IEC 60068-2-27
Relative Humidity	93 % without condensation conforming to IEC 60068-2-30
Electromagnetic Compatibility	Electrostatic discharge immunity test: (in contact), level 3, 6 kV, conforming to IEC 61000-4-2
	Electrostatic discharge immunity test: (in air), level 3, 8 kV, conforming to IEC 61000-4-2
	Susceptibility to electromagnetic fields: (80 MHz to 1 GHz), level 3, 10 V/m, conforming to IEC 61000-4-3
	Electrical fast transient/burst immunity test: (capacitive connecting clip), level 3, 1 kV, conforming to IEC 61000-4-4
	Electrical fast transient/burst immunity test: (direct), level 3, 2 kV, conforming to IEC 61000-4-4
	1.2/50 μs shock waves immunity test: (differential mode), level 3, 1 kV, conforming to IEC 61000-4-5
	1.2/50 μs shock waves immunity test: (common mode), level 3, 2 kV, conforming to IEC 61000-4-5
	Conducted RF disturbances: (0.1580 MHz), level 3, 10 V, conforming to IEC 61000-4-6
	Voltage dips and interruptions immunity test: (1 cycle), 0 %, conforming to IEC 61000-4-11
	Voltage dips and interruptions immunity test: (25/30 cycles), 70 %, conforming to IEC 61000-4-11
	Conducted and radiated emissions: , class B, conforming to EN 55022

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	2.8 cm
Package 1 Width	7.4 cm
Package 1 Length	9.4 cm
Package 1 Weight	80 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	40
Package 2 Height	15 cm
Package 2 Width	30 cm
Package 2 Length	40 cm
Package 2 Weight	3.706 kg

Life Is On Scheider

Sustainability Screen Premium

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Yes

Learn more about Green Premium >

Guide to assess a product's sustainability >



Transparency RoHS/REACh

Well-being performance




Rohs Exemption Information

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information


Dimensions Drawings

Width 17.5 mm




Connections and Schema

Internal Wiring Diagram



Wiring Diagram




Technical Description

Function C : Off-Delay Relay with Control Signal


Description

After power-up and closing of the control contact C, the output R closes. When control contact C re-opens, timing T starts. At the end of the timing period, the output(s) R revert(s) to its/their initial state. The second output can be either timed or instantaneous.

Function: 1 Output



Function: 2 Outputs



2 timed outputs (R1/R2) or 1 timed output (R1) and 1 instantaneous output (R2 inst.)

Legend

	Relay de-energised	
	Relay energised	
	Output open	
	Output closed	
с	Control contact	
G	Gate	
R	Relay or solid state output	
R1/R2	2 timed outputs	
R2 inst.	The second output is instantaneous if the right position is selected	
т	Timing period	
Ta -	Adjustable On-delay	
Tr -	Adjustable Off-delay	
U	Supply	