Product datasheet

Specification





Modicon M221, Analogue input cartridge, hoisting 2 analog I/O extension

TMC2HOIS01

Main

Range Of Product	Modicon M221
Product Or Component Type	Analogue input cartridge
Product Specific Application	Hoisting applications
Product Compatibility	Modicon M221C
Analogue Input Number	2

Complementary

<u> </u>		
Analogue Input Type	current 420 mA current 020 mA voltage 010 V	
Analogue Input Resolution	12 bits	
Lsb Value	2.44 mV 010 Vvoltage 4.88 μA 020 mAcurrent 3.91 μA 420 mAcurrent	
Conversion Time	20 ms	
Sampling Duration	10 ms	
Absolute Accuracy Error	+/- 0.1 % of full scale at 25 °C +/- 1 % of full scale	
Temperature Drift	+/- 0.02 %FS/°C	
Repeat Accuracy	+/- 0.5 %FS	
Non-Linearity	+/- 0.01 %FS	
Cross Talk	<= 1 LSB	
Type Of Cable	Twisted shielded pairs cable	
Electrical Connection	3 x 1.5 mm ² 2 screw terminal blocks with pitch 3.81 mm adjustment for inputs	
Maximum Cable Distance Between Devices	Twisted shielded pairs cable: <30 m for input	
Insulation	Non-insulated between analogue input and internal logic	
Height	41 mm	
Depth	15 mm	
Width	35 mm	
Net Weight	0.015 kg	
Permissible Continuous Overload	13 V, analogue input type: voltage 40 mA, analogue input type: current	
Input Impedance	<= 250 Ohm current >= 1 MOhm voltage	

Environment

Immunity To Microbreaks	10 ms		

Packing Units

Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	3.5 cm
Package 1 Width	4.6 cm
Package 1 Length	7.0 cm
Package 1 Weight	20.0 g
Unit Type Of Package 2	S02
Number Of Units In Package 2	75
Package 2 Height	15.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	3.305 kg



Green PremiumTM **label** is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >





Transparency RoHS/REACh

Well-being performance

Ø	Toxic Heavy Metal Free	
⊘	Mercury Free	
②	Rohs Exemption Information	Yes
⊘	Pvc Free	

Certifications & Standards

Reach Regulation	REACh Declaration
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation	China RoHS declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End of Life Information