

Altivar 320, Braking resistor, IP20, 280hm, 200W

VW3A7703

! Discontinued on: 1 Nov 2020

① Discontinued

Main

Range Of Product	Altivar
Range Compatibility	Altivar 61
	Altivar 312
	Altivar 32
	Altivar 312 Solar
	Altivar 31C
Product Compatibility	ATV312HD11N4
	ATV312HD11S6
	ATV312HD15N4
	ATV312HD15S6
	ATV312HU40M3
	ATV31CD11N4
	ATV31CD15N4
	ATV32HD11N4
	ATV32HD15N4
	ATV61HD18Y
	ATV61HD22Y
	ATV61HU30M3
	ATV61HU40M3
	ATV61WD15N4
	ATV61WD15N4C
	ATV61WD18N4
	ATV61WD18N4C
	ATV71HD11N4
	ATV71HD15N4
	ATV71HD15Y
	ATV71HD18Y
	ATV71HU30M3
	ATV71HU40M3
	ATV71PD11N4Z
	ATV71WD11N4
	ATV71WD15N4
	Variable speed drive ATV310 at 11 kW
Ohmic Value	28 Ohm
[Ue] Rated Operational Voltage	24 V DC at 0.1 A
	250 V AC at 1 A

Complementary

Average Power Available	200 W at 50 °C 231 W at 40 °C			
Electrical Connection	terminal, connection capacity: <= 1.5 mm² / AWG 16 for temperature control switch terminal, connection capacity: <= 4 mm² / AWG 28 for drive			
Temperature Controlled Switch Contact Resistance	60 μOhm			
Protection Type	Thermal protection via drive or temperature control switch at 120 °C			
Width	140 mm			
Height	393 mm			

Depth	120 mm	
Net Weight	3.5 kg	

Environment

Ip Degree Of Protection	IP20
Ambient Air Temperature For Storage	-2570 °C
Ambient Air Temperature For Operation	050 °C

Packing Units

9	
Unit Type Of Package 1	PCE
Number Of Units In Package 1	1
Package 1 Height	21.800 cm
Package 1 Width	25.800 cm
Package 1 Length	50.000 cm
Package 1 Weight	3.882 kg
Unit Type Of Package 2	S06
Number Of Units In Package 2	6
Package 2 Height	75.000 cm
Package 2 Width	60.000 cm
Package 2 Length	80.000 cm
Package 2 Weight	35.920 kg

Contractual warranty

Warranty 18 months

Sustainability

Green PremiumTM label is Schneider Electric's commitment to delivering products with best-inclass environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

Learn more about Green Premium >

Guide to assess a product's sustainability >


Well-being performance

	Reach Free Of Svhc	
②	Toxic Heavy Metal Free	
②	Mercury Free	
⊘	Rohs Exemption Information	Yes
Reac	h Regulation	REACh Declaration
Eu Rohs Directive		Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
China Rohs Regulation		China RoHS declaration

VW3A7703

Dimensions Drawings

Dimensions



Dimensions in mm

а	b	С	G	Н	Ø	
140	393	120	120	375	6 x 12	

Dimensions in in.

а	b	С	G	Н	Ø
5.51	15.47	4.72	4.72	14.76	0.24 X 0.47

VW3A7703

Mounting and Clearance

Clearance

