


Product datasheet

Specifications



empty elbowed control station - XAM-W - aluminium alloy - 5 cut- outs - grey

XAMWD05

⚠ Discontinued on: 1 Dec 2020

⚠ Discontinued

Main

Range Of Product	Harmony XAM
Product Or Component Type	Empty elbowed control station
Device Short Name	XAMW
Product Destination	For Ø 22 mm control and signalling units
Number Of Cut-Out	5 cut-outs
Colour Of Base Of Enclosure	Light grey (RAL 7035)
Colour Of Cover	Dark grey (RAL 7016)
Material	Aluminium alloy
Cable Entry	Via opening in rear of enclosure
Mounting Location	Flush mounting on vertical support
Product Mounting	Flush mounting on vertical support
Ip Degree Of Protection	IP65 conforming to IEC 60529
Resistance To Chemical Agents	Good resistant to acetone Good resistant to alcohols Good resistant to chloride and fluoride solvents Good resistant to diluted mineral acids Good resistant to oils and petrol Good resistant to organic acids Good resistant to salts

Complementary

Net Weight	0.79 kg
Flame Retardance	M3 conforming to CSTB VO conforming to UL 94

Environment

Protective Treatment	TC TH
Ambient Air Temperature For Storage	-40...70 °C
Ambient Air Temperature For Operation	-25...70 °C
Electrical Shock Protection Class	Class I conforming to IEC 60536
Overvoltage Category	Class I conforming to IEC 60536
Fire Resistance	850 °C conforming to NF C 20-455 960 °C conforming to IEC 92

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Standards	EN/IEC 60947-5-4
	EN/IEC 60947-5-1
	EN/IEC 60947-1

Contractual warranty

Warranty	18 months
----------	-----------