

Product datasheet

Specifications

contact block - standard contact blow-out - compatible with XKM



XKMA991

⚠ Discontinued on: 10 Oct 2022

⚠ Discontinued

Main

Product Or Component Type	Controllers separate parts
Accessory / Separate Part Category	Control accessory
Product Specific Application	Heavy hoisting applications
Product Compatibility	XKM
Accessory / Separate Part Type	Contact block
Number Of Contacts	4
Contact Blow-Out Type	Standard

Complementary

Electrical Connection	Screw clamp terminal, clamping capacity: 1 x 1.5...2 x 2.5 mm ²
Contact Operation	Slow-break Double-break
[Ith] Conventional Free Air Thermal Current	20 A conforming to IEC 337-1 20 A conforming to NF C 63-140 20 A conforming to VDE 0660
[Ui] Rated Insulation Voltage	500 V AC/DC conforming to IEC 158-1 500 V AC/DC conforming to NF C 20-040 500 V AC/DC conforming to VDE 0110 600 V conforming to CSA C22.2 No 14
Positive Opening	With
Maximum Resistance Across Terminals	25 MOhm at 1 A conforming to NF C 93-050
Short-Circuit Protection	20 A cartridge fuse type gG conforming to IEC 337-1B 20 A cartridge fuse type gG conforming to VDE 0660 part 2
Electrical Durability	3000000 cycles DC inductive load at 120 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 3000000 cycles DC inductive load at 24 V, power broken = 70 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5 3000000 cycles DC inductive load at 48 V, power broken = 75 conforming to IEC 337-1 DC-11, operating rate <60 cyc/mn 0.5
Net Weight	0.31 kg

Environment

Standards	CENELEC EN 50013
-----------	------------------

Packing Units

Unit Type Of Package 1	PCE
------------------------	-----

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Number Of Units In Package 1	1
Package 1 Height	5.5 cm
Package 1 Width	9.0 cm
Package 1 Length	15.5 cm
Package 1 Weight	321.0 g
Unit Type Of Package 2	S03
Number Of Units In Package 2	26
Package 2 Height	30.0 cm
Package 2 Width	30.0 cm
Package 2 Length	40.0 cm
Package 2 Weight	8.807 kg

Contractual warranty

Warranty	18 months
----------	-----------

Sustainability



Green Premium™ label is Schneider Electric's commitment to delivering products with best-in-class environmental performance. Green Premium promises compliance with the latest regulations, transparency on environmental impacts, as well as circular and low-CO₂ products.

Guide to assessing product sustainability is a white paper that clarifies global eco-label standards and how to interpret environmental declarations.

[Learn more about Green Premium >](#)

[Guide to assess a product's sustainability >](#)

Well-being performance

	Mercury Free	
	Rohs Exemption Information	Yes
Eu Rohs Directive	Pro-active compliance (Product out of EU RoHS legal scope)	
China Rohs Regulation	China RoHS declaration	